



**High Impact Resistance**



**High Tensile Strength**



**Excellent Adhesion To Substrate**



**Ideal for Panel & Dry Walls**

### AREA OF USE

- For most waterproofing emulsion
- For repairs of cracks
- For joints on pre-fabricated panel wall, dry wall, plaster ceiling

### ➤ Packaging

1m(w) x 100m(l) per Roll

### ➤ Outstanding Features

MVX Guard FG 100 has great strength and will not trap air that cause blisters and bubbles. It is easy to handle and minimise wastage.

### ➤ Shelf Life & Storage

Store in a cool-dry covered place and avoid direct exposure to sunlight.

MVX Guard FG 100 is a thin and high strength fibreglass mesh designed to provide strong reinforcement for joints on pre-fabricated panel wall, dry wall and plaster ceiling. It's high tensility reduces thermal deformation due to shrinkage and expansion of concrete.

As compared to common chopped strand mat, MVX Guard FG 100 reduces the constraint of working with loose and inconsistent distribution of strands. Hence, retaining the integrity of materials.

### TECHNICAL DATA

Properties	Typical Value
Odour & Appearance	Odourless Cloth Netting
Solubility	Non-soluble fibreglass
Combustibility	Non-combustible
Density (Count/inch)	Warp: ≈ 10   Weft: ≈ 10
Gross Weight	≈ 50gm/m <sup>2</sup>
Tensile Strength	Warp: ≈280N/50mm Weft: ≈300N/50mm